

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
19 May 2005 (19.05.2005)

PCT

(10) International Publication Number
WO 2005/045355 A1

(51) International Patent Classification⁷: **F42B 3/16**,
F42C 11/06, 15/31, 15/40

[RU/SE]; Noravägen 10 B, S-713 72 Gyttorp (SE). **DUMENKO, Aleksej** [RU/RU]; Plesheja dom. 15 kv.260, RU-127560 Moscow (RU).

(21) International Application Number:
PCT/SE2004/001585

(74) Agent: **AWAPATENT AB**; Box 45086, S-104 30 Stockholm (SE).

(22) International Filing Date:
3 November 2004 (03.11.2004)

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0302973-3 11 November 2003 (11.11.2003) SE

(71) Applicant (for all designated States except US): **DYNO NOBEL SWEDEN AB** [SE/SE]; Gyttorp, S-713 82 Nora (SE).


(72) Inventors; and

(75) Inventors/Applicants (for US only): **DUMENKO, Victor**

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: **POWER SOURCE**



(57) Abstract: The present invention provides a heat activated power source that comprises an anode element, a cathode element, and an electrolyte element, all of which are stacked in an electrically conductive shell so as to form a unitary body therein. The electrolyte is of a type that is ionically passive below a certain temperature and that is ionically active above that temperature. One of the anode and cathode elements serves the additional purpose of providing for heat amplification, and thus amplifies an otherwise too small heat energy signal so that it is enough for activating the electrolyte. The power source is particularly suitable for use in pyro-electric detonator applications, where it facilitates highly accurate delay times that are virtually independent of the delay time duration. The power source is suitable for large scale manufacturing, with maintained time delay performance and without need for special manufacturing equipment-or for inert gas conditions.

WO 2005/045355 A1



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— *of inventorship (Rule 4.17(iv)) for US only*

Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.